

DESCRIPTION	protective polishing wax for use over Sigmulto Pharos and Sigmulto Amouage
PRINCIPAL CHARACTERISTICS	<ul style="list-style-type: none"> - for interior use - unsaponifiable and alkaline resistant - low odour - provides a highly polished finish for Sigmulto Pharos offering a higher level of protection to the finish - easy to apply
COLOUR AND GLOSS	opaque – gloss
BASIC DATA AT 20 °C	
Mass density	approx. 0.79 g/cm ³
Viscosity	solid, paste like
Theoretical spreading rate	approx. 3.2 g/m ² depending on the amount of wax applied and the application method employed
Touch dry after	approx. 1 hour
Shelf life (cool, dry place)	24 months
Flashpoint	above 65 °C
Available pack size	4.5 oz (125 g)
SYSTEM SPECIFICATION	<p>Sigmulto Pharos Wax should be applied after Sigmulto Pharos or, if applied, the Sigmulto Amouage, has fully dried. The wax should be applied with a clean, dry cloth using a circular motion.</p> <p>Care should be taken to avoid overthick application as this will result in a thicker wax layer making the final polishing more difficult</p>
INSTRUCTIONS FOR USE	
<u>CLOTH</u> Recommended thinner	apply by clean dry cloth using a circular motion not to be thinned
<u>CLEANING SOLVENT</u>	Sigma thinner 20-05
SAFETY PRECAUTIONS	 see safety sheet 1570 for information on LEL and TLV values
REFERENCES	explanation to product data sheets on information sheet 1551